# Launch Vehicle/Reentry Vehicle (LV/RV) National Airspace System (NAS) Effect Assessment

Center of Excellence for Commercial Space Transportation

5<sup>th</sup> Annual Technical Meeting October 26-28, 2015





#### **Background**

Demand for space access for commercial, civilian and military use has been rising rapidly.

FAA accommodates space launches often by blocking large volumes of airspace from traditional National Airspace System (NAS) usage. This results in flights routing around blocked airspace resulting in extra flying distance and delays.

FAA has asked for insights into the effects of upcoming launches on the NAS to balance competing demands in a safe and efficient manner



# What is the Effect of A Proposed Future LVRV Operation on the Other NAS Users?

### Example of Flight Rerouting During Actual Launch




Image source: All NAS Display, MITRE Corporation

#### Current FAA Practice:

- Use manual analysis of Traffic Situation
   Display (TSD) replays for a few sample days
   to estimate impact of proposed operation on
   future day in terms of flight counts
- This analysis is input to decision making process and in any negotiations between the FAA and the space operator

#### MITRE recommended to the FAA the following improvements:

- Use objective, repeatable, model-based approach to look at the distribution of likely impacts over a large sample of historical dates similar to the proposed date
- Consider number of impacted flights, expected increase in flying time, or possible ground delay, and the likely range for these values
- Include ability to perform detailed time period and sensitivity analysis
- FAA accepted these recommendations



## **Technical Approach**


- Historical Date Selection for Input to Simulation Model
  - Pick sample of 30 historical days most similar to the proposed launch date
- Simulating Effect of the Launch on Other NAS Users Over the Selected Dates
  - Avoid active Aircraft Hazard Area (AHA) by ground delay, or by routing around them
  - Reroute using minimum deviation around AHAs
  - Impact metrics
    - Number of affected flights
    - Extra distance travelled

- Delay experienced
- For each metric
  - The average value
  - Likely range of the average
  - The likely maximum value
- Model Performance
  - Completes on "standard PC" in 1-2 hours or less
  - Preprocessing to speed-up run time
- Based on Alternative TFM Actions Model (ATAM) software
  - Developed previously for AJR
  - Extensively revised for LVRV application



#### **Example: NASA ORION Launch**


(Launched from Cape Canaveral on 5<sup>th</sup> December, 2014)



Background Image source: Google Earth, product of Google Inc.




## **Example: Actual Flights Intersecting Launch AHA on Historical Date**






## **Example: Flights Rerouted Around Launch AHA and SUAs**






## What Happens if the Launch Or Recovery Time Window is Changed?







- Base Analysis: Impact on 30 similar historical dates
- Alternative Dates?: Look at likely back-up dates
- Alternative Start Times?: Change time by +/- 3 hours
- Time Period Analysis?
  - Look at effect by 15-minute interval in within base case time window
  - See impact of each AHA separately
- Data to answer all these questions is pre-generated during the simulation run





### **NOTICE**

This work was produced for the U.S. Government under Contract DTFAWA-10-C-00080 and is subject to Federal Aviation Administration Acquisition Management System Clause 3.5-13, Rights In Data-General, Alt. III and Alt. IV (Oct. 1996).

The contents of this document reflect the views of the author and The MITRE Corporation and do not necessarily reflect the views of the Federal Aviation Administration (FAA) or the Department of Transportation (DOT). Neither the FAA nor the DOT makes any warranty or guarantee, expressed or implied, concerning the content or accuracy of these views.

© 2015 The MITRE Corporation. All Rights Reserved.

