Flood Inundation Mapping Projects

Jeremiah Lant, Hydrologist, USGS
Kentucky Water Science Center
jlant@usgs.gov

Outline

- Flood inundation projects in Kentucky
- Overview of general steps involved in flood inundation projects
- Closer look at the Frankfort, Kentucky flood inundation project

Acknowledgements

- Thank you Kentucky Geological Survey for the opportunity to present at the 2014 Annual Meeting.

Flood Inundation Projects in Kentucky

Hopkinsville, Kentucky

USGS
science for a changing world

Prepared in cooperation with the City of Hopkinsville, Kentucky, Community Development Services

Flood-Inundation Maps for an 8.9-Mile Reach of the South Fork Little River at Hopkinsville, Kentucky

Pamphlet to accompany
Scientific Investigations Map 3242

U.S. Department of the Interior
U.S. Geological Survey

http://pubs.usgs.gov/sim/3242/

Frankfort, Kentucky

USGS
science for a changing world

Prepared in cooperation with City of Frankfort, Kentucky, Office of Emergency Management

Flood-Inundation Maps for a 6.5-Mile Reach of the Kentucky River at Frankfort, Kentucky

Pamphlet to accompany
Scientific Investigations Map 3278

U.S. Department of the Interior
U.S. Geological Survey

http://pubs.usgs.gov/sim/3278/

Flood Inundation Project Objectives

- **Develop** detailed libraries of flood inundation maps for a river reach of interest.
- **Use** the flood inundation maps in conjunction with the National Weather Service (NWS) Advanced Hydrologic Prediction Service flood warning system to show predicted areas of flood inundation.
  - **Helps with** preplanning **flood response** and **early flood warning**
- **Provide** online portals for the public to view USGS flood inundation study information and interact with the flood inundation map libraries.

- **The flood inundation maps,** along with online information regarding current stages from USGS streamgage and forecasted stages from the NWS, provide emergency management and local residents with **critical information for flood response activities.**

Flood Inundation Project Phases

- **Phase 1** – Project Scoping and Planning
  - Site selection, modeling approach, and data collection
- **Phase 2A** – Hydraulic Analyses
  - Build and calibrate hydraulic model
- **Phase 2B** – Mapping
  - Create and submit map products to NWS and USGS Flood Inundation Mapping Program (FIMI)
- **Phase 3** – USGS Flood Inundation Mapping Science (FIMI) and NWS Advanced Hydrologic Prediction Service (AHPS) Web Implementation
  - Put maps on the Internet

USGS Streamgage

USGS streamgage(s) within study domain







Scoping/Approach, Data Collection, Modeling

Study Area



+

Digital Terrain/Elevation Model



+

FEMA Flood Insurance Study



+

Bathymetry and/or survey data



+

Hydraulic Model and Calibration



=

Flood Inundation Depth Grid



Mapping and Web Implementation



Final Products – USGS Published Maps



USGS
science for a changing world

U.S. Department of the Interior
U.S. Geological Survey

Prepared in cooperation with the
City of Hopkinsville, Kentucky

Scientific Investigations Map 3242
Sheet 13 of 13
Pamphlet accompanies map

Hopkinsville

South Fork Little River

EXPLANATION

Flood-inundation Map for Hopkinsville, Kentucky
Corresponding to a Stage of 21.50 Feet and an
Elevation of 545.50 Feet (NAVD 88) at
U.S. Geological Survey Streamgage Number 03437495
South Fork Little River at Highway 68 By-Pass

By
Jeremiah Lant
2012

Final Products – USGS Flood Inundation Mapper



http://wim.usgs.gov/FIMI/FloodInundationMapper.html

Frankfort, KY – Flood Inundation Project

Study Area



1978 Flood

Frankfort, Kentucky – Data Collection and Processing

Raw bathymetry data

Processed bathymetry data and NLD data





Raw Points – Blue
Projected Points – Green
Smoothed Points - Red



Frankfort, KY - Modeling Approach

	Stage (ft.)	Elevation (ft.) NAVD88
Highest inundation Stage:	52	513.58
Major Flood Stage:	40	501.58
Moderate Flood Stage:	35	496.58
Flood Stage:	31	492.58
Action Stage:	29	490.58
Lowest inundation Stage:	27	488.58
Gage 0 Datum:	0	461.58

Mapping Interval (ft): 1.0

List of Modeled Stages (ft): 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52

FEMA Elevations for 10, 2, 1, 0.2 % Flood: 10% = 496.0 ft, 2% = 503.0 ft, 1% = 508.0 ft, 0.2% = 510.0 ft

Frankfort, Kentucky - Model Calibration
Stage Discharge Rating

- **Criteria: Water surface profiles are to be within +- 0.5 ft. of the established USGS stage discharge rating.**



Frankfort, Kentucky - Model Calibration
2010 Flood Event with High Water Marks

- **Criteria: Water surface profiles are to be within +- 1.0 ft. of the measured high water marks.**





Phases 2B – 3: Frankfort, KY Web Implementation
USGS Flood Inundation Mapper



http://wim.usgs.gov/FIMI/FloodInundationMapper.html

Frankfort, Kentucky - NWS Flood Inundation Mapper



http://water.weather.gov/ahps2/inundation/inundation_google.php?g_datatype=depth&wfo=lmk&gage=fftk2

Questions?