



NR01-L 4-Component Net Radiometer



Research Grade

Robust 4-way radiometer that requires little maintenance

Overview

The NR01, manufactured by Hukseflux and cabled for use with Campbell Scientific data loggers, is a research-grade net radiometer that measures the energy balance between incoming short-wave and long-wave infrared radiation versus surface-reflected short-wave and outgoing long-wave infrared radiation. Our data loggers measure the NR01's output and control its internal heater. This net radiometer offers a

professional solution for scientific-grade energy balance studies.

Note: NR01 radiometers with a serial number less than 2313 used the pn 21271 fitting. NR01 radiometers with a serial number greater than 2312 do not need the pn 21271 fitting.

Benefits and Features

- › Internal RTD provides temperature compensation of measurements
- › Research-grade performance
- › Internal 1-W heater reduces formation of dew and melts frost
- › Separate outputs of short-wave and long-wave infrared radiation for better accuracy and more thorough quality assurance
- › Robust—only requiring limited maintenance

Detailed Description

The NR01 consists of a pyranometer and pyrgeometer pair that faces upward and a complementary pair that faces downward. The pyranometers and pyrgeometers measure short-wave and far infrared radiation, respectively.

The NR01 includes an on-board RTD to measure the radiometer's internal temperature and a 1-W heater that minimizes the formation of dew and melts frost. To reduce

current drain, a relay is typically used to turn on the heater only when the solar radiation is less than 20 W/m².

Campbell Scientific's CR6 and CR3000 dataloggers can directly measure this radiometer. A CR1000 can also be used, but a 4WPB100 module is required to measure the internal RTD.

Specifications

Sensor	Hukseflux's SR01 ISO-class, thermopile pyranometers, IR01 pyrgeometers, PT100 RTD
Measurement Description	Measures incoming and outgoing short-wave and long-wave radiation
Response Time	18 s
Sensitivity	10 to 40 $\mu\text{V W}^{-1} \text{m}^2$
Expected Output Range	-0.1 to +50 mV
Expected Accuracy for Daily Totals	$\pm 10\%$
Heater	90 ohm, 1.6 W (at 12 Vdc)

Operating Temperature Range	-40° to +80°C
Heater Current Drain	~140 mA
Dimensions	26.3 x 11.3 x 12.1 cm (10.4 x 4.4 x 4.8 in.)
Weight	› 1.3 kg (2.9 lb) with 5 m (16.4 ft) cable › 0.9 kg (2 lb) sensor only

Pyranometer

Spectral Range	305 to 2800 nm
----------------	----------------

Pyrgeometer

Spectral Range	4500 to 50,000 nm
----------------	-------------------

For comprehensive details, visit: www.campbellsci.com/nr01 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2020 Campbell Scientific, Inc. | 06/23/2020