

# **Automatic Analysis method**

September 18<sup>th</sup>, 2023 8<sup>th</sup> Joint Project Team Meeting Jakarta, Indonesia

Japan Aerospace Exploration Agency (JAXA) **Yuki TAKAKURA** 



## **SAR** image-derived information

Information we can provide to users	Process	Time (from observation to end of processing)
RGB composite image (★) <flooding> Location of the flood extent (★)</flooding>	Auto	2 hour
<flooding>     - Location of the flood extent (★) (SM3 mode only)     - Area of flood by each municipality (Japan only)     - Number of flooded buildings by each municipality (Japan only)</flooding>	Auto	2.5 hour (Japan) 0.5 hour (Other)
<earthquakes> (Japan only) - Location of damaged-buildings - Number of damaged-buildings by each municipality</earthquakes>	Martinesters of the second of	

(★) Information currently provided by JAXA to Sentinel Asia



# Optical image-derived information


Information we can provide to users	Process	Time (from observation to end of processing)
<pre><flooding> - Location of the flood extent (Under verification)</flooding></pre>	Auto	2 hour
<landslide> - Location of the landslide extent (Under verification)</landslide>		



# SAR imagery



JAXA has developed a system to automatically detect the flood extent using JAXA's ALOS-2 data for Sentinel Asia.



Flood in Pakistan on 17 August, 2022

#### > Benefit:

When an EOR is activated and observations are made by ALOS-2, JAXA can now quickly provide extracted flood-area information as well as ALOS-2 observation imagery.

#### Analysis Method:


This analysis uses a simple and primitive SAR analysis method and is fully automated. (Therefore, the accuracy may be lower than that of other DANs that use more sophisticated analysis methods.)

#### **Notice**

- The information is automatically estimated from satellite data and could differ from the actual flood extent.
- It shows estimated flood extent at the time of satellite observation and does not indicate the maximum extent.



A **simple and primitive method** of extracting the flood extent by automatically determining the threshold of water from the **backscatter intensity** of the ALOS-2 (SAR) image.





Storm, Flood and Landslide in Vietnam on 28 September, 2022 JAXA's VAP is almost same as AIT's and EOS's ALOS-2, ScanSAR mode **EOS** JAXA **AIT** ©EOS-RS, ARIA, NASA-JPL/Caltech, JAXA



#### Cyclone MOCHA in Myanmar on 14 May, 2023

ALOS-2, ScanSAR mode

https://storymaps.arcgis.com/collections/6c2cdd4f4b92434cbb6d343eaa0006db?item=1

**JAXA EOS AIT** ©EOS RS, ARIA, NASA-JPL/Caltech, JAXA

©EOS-RS, ARIA, NASA-JPL/Caltech,





### Flood, Landslide and Storm in India on 13 July, 2023

https://storymaps.arcgis.com/collections/9ee0925945ec4659b107b814c2f99b5e?item=1

JAXA

AIT





ALOS-2, ScanSAR mode



### JAXA is developing another automated system with higher accuracy.

This system requires ALOS-2 L1.1 data, which is closer to raw data than ALOS-2 L2.1 data used in the algorithm introduces earlier, for analysis. This method is expected to be more accurate especially for urban area.


This method is currently being validated and may be replaced by this method in the future.

#### **Notice**

- The information is automatically estimated from satellite data and may differ from the actual flood extent.
- It shows estimated flood extent at the time of satellite observation and does not indicate the maximum extent.



Use L1.1 data and perform interference analysis to improve accuracy especially in urban areas. Based on Ohki et al. (2020).






## Typhoon Mawar in Philippines on 27 May, 2023


ALOS-2, SM3 mode


JAXA (New method, L1.1)





JAXA (Conventional method, L2.1)








### Flood in Andhra Pradesh, India on 12 July, 2022

ALOS-2, SM3 mode

https://sentinel-asia.org/EO/2022/article20220712IN.html

JAXA (New method, L1.1)



JAXA (Conventional method, L2.1)






# Optical imagery




## **Automatic Analysis for Flood by Optical image**

A **simple and primitive method** of extracting the flood extent by automatically determining the threshold of water from the NDVI or NIR of the optical image.





## **Automatic Analysis for Flood by Optical image**




NDVI: Normalized Difference Vegetation Index


NIR: Near infrared

Blue: Estimated flood extent

Yellow: Grand truth by Geospatial Information Authority

of Japan (GSI) (as of 10/14)







## Summary

JAXA is developing automatic analysis systems to extract affected areas using SAR and optical imagery.

#### **SAR** imagery:

JAXA have already provided VAPs of the automatically estimated flood extent to Sentinel Asia.

We are also working to improve its accuracy.

#### Optical imagery:

Primitive and automatic methods have already been implemented. Automatic analysis using deep learning is also under study.

#### Issue:

Lack of ground-truth data makes it difficult to assess the accuracy of VAPs. As a DAN, I would appreciate it if anyone who has grand truth data such as flood extent, location of landslides, location of building damage, etc., could share it with Sentinel Asia, because it will help improve the accuracy of DAN's VAP.