



XMPP

<mailto:kevin.smith@isode.com>
<xmpp:kevin.smith@isode.com>

<mailto:steve.kille@isode.com>
<xmpp:steve.kille@isode.com>

Status	Type	Short Name
--------	------	------------

Legal

Copyright

Permissions

Warranty

Liability

Conformance

<https://xmpp.org/about/xsf/ipr-policy>

Contents

1	Introduction	1
2	Use Cases	2
3	Internationalization Considerations	13
4	Security Considerations	13
5	IANA Considerations	14
6	XMPP Registrar Considerations	14
7	XML Schema	14
8	Acknowledgements	14

1 Introduction

2 Use Cases

2.1 Server Identification of MIX Capable Clients

2.2 Messages From MIX Channels

[s.ietf.org/html/rfc6121](https://www.ietf.org/html/rfc6121)

<https://xmpp.org/extensions/xep-0376.html>
<https://xmpp.org/extensions/xep-0369.html>

<http://tools>

```
<message from='coven@mix.shakespeare.example/123456'  
  to='hecate@shakespeare.example'  
  id='77E07BB0-55CF-4BD4-890E-3F7C0E686BB0'  
  type='groupchat'>  
  <body>Harpier cries: 'tis_time, 'tis time.</body>  
  <mix xmlns='urn:xmpp:mix:core:1'>  
    <nick>thirdwitch</nick>  
    <jid>hag66@shakespeare.example</jid>  
  </mix>  
</message>
```

```
<message from='coven@mix.shakespeare.example/123456'  
  to='hecate@shakespeare.example/UUID-x4r/2491'  
  id='77E07BB0-55CF-4BD4-890E-3F7C0E686BB0'  
  type='groupchat'>  
  <body>Harpier cries: 'tis_time, 'tis time.</body>  
  <mix xmlns='urn:xmpp:mix:core:1'>  
    <nick>thirdwitch</nick>  
    <jid>hag66@shakespeare.example</jid>  
  </mix>  
</message>  
  
<message from='coven@mix.shakespeare.example/123456'  
  to='hecate@shakespeare.example/UUID-b5b/0114'  
  id='77E07BB0-55CF-4BD4-890E-3F7C0E686BB0'  
  type='groupchat'>  
  <body>Harpier cries: 'tis_time, 'tis time.</body>  
  <mix xmlns='urn:xmpp:mix:core:1'>  
    <nick>thirdwitch</nick>  
    <jid>hag66@shakespeare.example</jid>  
  </mix>  
</message>
```

2.3 Messages To MIX Channels

2.4 Client Determines MIX Capability of Client's Server

```
<iq from='hag66@shakespeare.example/UUID-c8y/1573'  
  id='lx09df27'  
  type='get'>  
  <query xmlns='http://jabber.org/protocol/disco#info' />  
</iq>  
  
<iq id='lx09df27'  
  to='hag66@shakespeare.example/UUID-c8y/1573'  
  type='result'>  
  <query xmlns='http://jabber.org/protocol/disco#info'>  
    <feature var='urn:xmpp:mix:pam:2' />  
    <feature var='urn:xmpp:mix:pam:2#archive' />  
  </query>  
</iq>
```

2.5 MIX Management and Discovery

2.6 MIX Join and Leave Support on Local Server

2.7 Joining a Channel

```
<iq type='set'  
  from='hag66@shakespeare.example/UUID-a1j/7533'  
  to='hag66@shakespeare.example'  
  id='E6E10350-76CF-40C6-B91B-1EA08C332FC7'>  
  <client-join xmlns='urn:xmpp:mix:pam:2' channel='coven@mix.  
    shakespeare.example'>  
    <join xmlns='urn:xmpp:mix:core:1'>  
      <subscribe node='urn:xmpp:mix:nodes:messages' />  
      <subscribe node='urn:xmpp:mix:nodes:presence' />  
      <subscribe node='urn:xmpp:mix:nodes:participants' />  
      <subscribe node='urn:xmpp:mix:nodes:info' />  
    </join>  
  </client-join>  
</iq>
```

```
<iq type='set'  
  from='hag66@shakespeare.example'  
  to='coven@mix.shakespeare.example'  
  id='E6E10350-76CF-40C6-B91B-1EA08C332FC7'>  
  <join xmlns='urn:xmpp:mix:core:1'>  
    <subscribe node='urn:xmpp:mix:nodes:messages' />  
    <subscribe node='urn:xmpp:mix:nodes:presence' />  
  </join>  
</iq>
```

<https://xmpp.org/extensions/xep-0369.html>

<https://xmpp.org/extensions/xep-0369.html>

<https://xmpp.org/extensions/xep-0369.html>


```
<subscribe node='urn:xmpp:mix:nodes:participants' />
<subscribe node='urn:xmpp:mix:nodes:info' />
</join>
</iq>
```

```
<iq type='result'
  from='coven@mix.shakespeare.example'
  to='hag66@shakespeare.example'
  id='E6E10350-76CF-40C6-B91B-1EA08C332FC7'>
  <join xmlns='urn:xmpp:mix:core:1' jid='123456#coven@mix.shakespeare.
    example'>
    <subscribe node='urn:xmpp:mix:nodes:messages' />
    <subscribe node='urn:xmpp:mix:nodes:presence' />
    <subscribe node='urn:xmpp:mix:nodes:participants' />
    <subscribe node='urn:xmpp:mix:nodes:info' />
  </join>
</iq>
```

```
<iq type='result'
  from='hag66@shakespeare.example'
  to='hag66@shakespeare.example/UUID-a1j/7533'
  id='E6E10350-76CF-40C6-B91B-1EA08C332FC7'>
  <client-join xmlns='urn:xmpp:mix:pam:2'>
    <join xmlns='urn:xmpp:mix:core:1'
      jid='123456#coven@mix.shakespeare.example'>
      <subscribe node='urn:xmpp:mix:nodes:messages' />
      <subscribe node='urn:xmpp:mix:nodes:presence' />
      <subscribe node='urn:xmpp:mix:nodes:participants' />
      <subscribe node='urn:xmpp:mix:nodes:info' />
    </join>
  </client-join>
</iq>
```

2.8 Leaving a Channel

```
<iq type='set'
  from='hag66@shakespeare.example/UUID-a1j/7533'
  to='hag66@shakespeare.example'
  id='E6E10350-76CF-40C6-B91B-1EA08C332FC7'>
  <client-leave xmlns='urn:xmpp:mix:pam:2'
    channel='coven@mix.shakespeare.example'>
    <leave xmlns='urn:xmpp:mix:core:1' />
  </client-leave>
</iq>
```

```
<iq type='set'
  from='hag66@shakespeare.example'
  to='coven@mix.shakespeare.example'
  id='E6E10350-76CF-40C6-B91B-1EA08C332FC7'>
  <leave xmlns='urn:xmpp:mix:core:1' />
</iq>
```

```
<iq type='result'
  from='coven@mix.shakespeare.example'
  to='hag66@shakespeare.example'
```

<https://xmpp.org/extensions/xep-0369.html>
<https://xmpp.org/extensions/xep-0369.html>
<https://xmpp.org/extensions/xep-0369.html>
<https://xmpp.org/extensions/xep-0369.html>

```
    id='E6E10350-76CF-40C6-B91B-1EA08C332FC7'>
  <leave xmlns='urn:xmpp:mix:core:1' />
</iq>
```

```
<iq type='result'
  from='hag66@shakespeare.example'
  to='hag66@shakespeare.example/UUID-a1j/7533'
  id='E6E10350-76CF-40C6-B91B-1EA08C332FC7'>
  <client-leave xmlns='urn:xmpp:mix:pam:2'>
    <leave xmlns='urn:xmpp:mix:core:1' />
  </client-leave>
</iq>
```

2.9 Roster Management

2.9.1 Setting User Presence

```
<presence xmlns='jabber:client' from='hag66@shakespeare.example/UUID-  
a1j/7533'>  
  <show>dnd</show>  
  <status>Making a Brew</status>  
</presence>
```

403.html

<https://xmpp.org/extensions/xep-0084.html>

<https://xmpp.org/extensions/xep-0>

<https://xmpp.org/extensions/xep-0045.html>

<https://xmpp.org/extensions/xep-0369.html>

```
<presence from='hag66@shakespeare.example/UUID-a1j/7533'
          to='coven@mix.shakespeare.example'>
  <show>dnd</show>
  <status>Making a Brew</status>
</presence>
```

2.9.2 Receiving User Presence

```
<presence from='123435#coven@mix.shakespeare.example/UUID-a1j/7533'
          to='hag99@shakespeare.example'
          id='77E07BB0-55CF-4BD4-890E-3F7C0E686BBD'>
  <mix xmlns='urn:xmpp:mix:presence:0'>
    <jid>hecate@shakespeare.example/UUID-x4r/2491</jid>
    <nick>thirdwitch</nick>
  </mix>
  <show>dnd</show>
  <status>Making a Brew</status>
</presence>
```

```
<presence from='123435#coven@mix.shakespeare.example/UUID-a1j/7533'
          to='hag99@shakespeare.example/UUID-rrr/1234'
          id='77E07BB0-55CF-4BD4-890E-3F7C0E686BBD'>
  <mix xmlns='urn:xmpp:mix:presence:0'>
    <jid>hecate@shakespeare.example/UUID-x4r/2491</jid>
    <nick>thirdwitch</nick>
  </mix>
  <show>dnd</show>
  <status>Making a Brew</status>
</presence>
```

2.9.3 Client Coming Online and Obtaining Presence from the Local Server

2.9.4 Going Offline

```
<presence type='unavailable'  
  from='hag66@shakespeare.example/UUID-a1j/7533'  
  to='coven@mix.shakespeare.example' />
```

2.10 MIX Roster Item Capability Sharing

```
<iq from='juliet@example.com/balcony'  
  id='bv1bs71f'  
  type='get'>  
  <query xmlns='jabber:iq:roster'>  
    <annotate xmlns='urn:xmpp:mix:roster:0' />  
  </query>  
</iq>
```

```
<item jid='romeo@example.net' />
```

```
<item jid='balcony@example.net'>  
  <channel xmlns='urn:xmpp:mix:roster:0' participant-id='123456' />  
</item>
```

2.11 MAM Archive Support

2.12 Blocking Considerations

3 Internationalization Considerations

4 Security Considerations

5 IANA Considerations

6 XMPP Registrar Considerations

7 XML Schema

8 Acknowledgements