



SHERWIN-WILLIAMS.



Warehouse / Distribution / Manufacturing Facility Guide Specification

This Painting Schedule is furnished as a guide to select paint systems, and is not all-inclusive of available Sherwin-Williams products. Specifiers should review the contents and edit to suit the particular project and its location.

The schedule is arranged by substrates, and offers latex, acrylic, water-based epoxy, and water-based urethane. Each type also includes the available sheens.

Local and National V.O.C. (Volatile Organic Compound) regulations have been taken into consideration. However, because regulations vary by region and frequently change, specifiers should verify that the products comply with local rules. Consult with your Sherwin-Williams representative before finalizing the selection.

If you need additional product information, contact your Sherwin-Williams representative, refer to the Sherwin-Williams Painting Systems Catalog, visit sherwin-williams.com or call our Architectural Services Answer Team.

The Sherwin-Williams Company
Architectural Services Department
800-321-8194 (Telephone)
216-566-1392 (Fax)
specifications@sherwin.com (Email)

**09 91 23 INTERIOR &
09 91 13 EXTERIOR**

Issued July 2015

The Sherwin-Williams Company

**Download this document at
www.swspecs.com**



Table of Contents

INTERIOR SYSTEMS:

Important Surface Preparation Instructions:	Page 3
Interior Topcoats:	Page 3
Miscellaneous Notes:	Page 4
Lobby / Common Area:	Pages 5 – 7
CMU — Concrete Masonry Units	
Masonry and Concrete — Ceilings and Soffits	
Gypsum Board — Walls	
Gypsum Board — Ceilings and Soffits	
Wood — Painted Doors, Frames, Trim and Chair Rails	
Wood — Stained Doors, Frames, Trim and Chair Rails	
Ferrous Metal — Doors, Frames and Miscellaneous Metals	
Ferrous Metal — High Performance Finish for Handrails	
Non-Ferrous Metal — Galvanized/Aluminum Surfaces	
Non-Ferrous Metal — High Performance Finish for Handrails	
Food Area / Restroom / Corridor:	Pages 7 – 8
CMU — Concrete Masonry Units	
Masonry and Concrete — Ceilings and Soffits	
Gypsum Board — Walls	
Gypsum Board — Ceilings and Soffits	
Ferrous Metal — Doors, Frames and Miscellaneous Metals	
Ferrous Metal — High Performance Finish for Handrails	
Non-Ferrous Metal — Galvanized/Aluminum Surfaces	
Non-Ferrous Metal — High Performance Finish for Handrails	
Cubicle / Office / Conference Room / Break Room:	Pages 9 – 10
Gypsum Board — Ceilings and Soffits	
Gypsum Board — Walls	
Ferrous Metal — Doors, Frames and Miscellaneous Metals	
Ferrous Metal — High Performance Finish for Handrails	
Non-Ferrous Metal — Galvanized/Aluminum Surfaces	
Non-Ferrous Metal — High Performance Finish for Handrails	
Manufacturing / Warehouse / Distribution:	Page 11
CMU — Concrete Masonry Unit Walls	
Masonry Walls	
Ferrous Ceiling Decking — Including Bar Joists	
Non-Ferrous Decking	
Ferrous Metal — Doors, Frames and Miscellaneous Metals	
Ferrous Metal — High Performance Finish for Handrails	
Concrete Floors — Clear, Pigmented & Decorative:	Page 12
Light Duty (Foot Traffic)	
Medium/Heavy Duty (Kitchen Areas, Food Service, Restrooms, Labs, Warehouse, Corridors)	
Heavy Traffic Areas (Premium Performance)	

Table of Contents (Cont.)

EXTERIOR SYSTEMS:

Exterior Topcoats:	Page 13
Exterior Tilt-Up Concrete / Masonry Areas (Smooth):	Page 14
Exterior CMU & Block Areas (Porous):	Page 14
Exterior Ferrous Metals:	Page 15
Exterior Non-Ferrous Metals:	Page 15
Exterior Wood:	Page 15
Exterior Plaster / Stucco:	Page 16

Warehouse/Distribution/Manufacturing Facility Interior Paint Schedule

Important Surface Preparation Instructions:

Verify the existence of lead based paints on the project. Buildings constructed after 1978 are less likely to contain lead based paints. If lead based paints are suspected on the project, all removal must be done in accordance with the EPA Renovation, Repair and Painting Rule and all applicable state and local regulations. State and local regulations may be more strict than those set under the federal regulations. Verify that Owner has completed a Hazardous Material Assessment Report for the project prior to issuing of Drawings.

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority. Removal must be done in accordance with EPA Renovation, Repair and Painting Rule and all related state and local regulations. Care should be taken to follow all state and local regulations which may be more strict than those set under the federal RRP Rule.

Specifier Notes — Topcoats:

- a. **ProMar® 200 Zero VOC Interior Latex** — A durable, professional quality zero VOC vinyl acrylic topcoat available in a Flat, Low Sheen, Eg-Shel, and Semi-Gloss finish.
- b. **Pro Industrial™ Pre-Catalyzed Waterbased Epoxy** — A single component, waterbased acrylic epoxy that offers the durability and resistance to stains and most cleaning solvents usually characteristic of two-component waterbased epoxies. Available in an Eg-Shel and Semi-Gloss finish.
- c. **Pro Industrial™ Water Based Catalyzed Epoxy** — A two-component, water-based epoxy formulated to provide excellent corrosion resistance, chemical resistance, abrasion resistance, and moisture resistance. Available in an Eg-Shel and Gloss finish.
- d. **Pro Industrial™ Acrylic Coating** — A single component, light industrial, 100% acrylic coating that flows and levels to a smooth finish. Available in an Eg-Shel, Semi-Gloss, and Gloss finish.
- e. **Pro Industrial™ Multi-Surface Acrylic** — An interior and exterior waterborne acrylic for use on marginally prepared metal or masonry surfaces. Fast drying, easy application with dryfall properties. Available in an Eg-Shel and Gloss finish.
- f. **Pro Industrial™ Waterborne Acrylic Dryfall** — A dryfall for use on exposed ceilings and overhead surfaces in commercial, warehouse and manufacturing facilities. Available in a Flat, Eg-Shel, and Semi-Gloss finishes.

Recommended Finishes:

Ceilings and Soffits:	Flat Finish
Walls:	Eg-Shel or Semi-Gloss Finish
Trim:	Semi-Gloss Finish (unless otherwise noted)

Miscellaneous Notes:

SURFACE PREPARATION:

- A. Proper product selection, surface preparation, and application affect coating performance. Coating integrity and service life will be reduced because of improperly prepared surfaces. Selection and implementation of proper surface preparation ensures coating adhesion to the substrate and prolongs the service life of the coating system.
- B. Selection of the proper method of surface preparation depends on the substrate, the environment, and the expected service life of the coating system. Economics, surface contamination, and the effect on the substrate will also influence the selection of surface preparation methods.
- C. The surface must be dry and in sound condition. Remove oil, dust, dirt, loose rust, peeling paint or other contamination to ensure good adhesion.
- D. Remove mildew before painting by washing with a solution of 1 part liquid household bleach and 3 parts of warm water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with clean water and allow the surface to dry 48 hours before painting. Wear protective glasses or goggles, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.
- E. Previously Coated Surfaces: maintenance painting will frequently not permit or require complete removal of all old coatings prior to repainting. However, all surface contamination such as oil, grease, loose paint, mill scale, dirt, foreign matter, rust, mold, mildew, mortar, efflorescence, and sealers must be removed to assure sound bonding to the tightly adhering old paint. Glossy surfaces of old paint films must be clean and dull before repainting. Thorough washing with an abrasive cleanser will clean and dull in one operation, or, wash thoroughly and dull by sanding. Spot prime any bare areas with an appropriate primer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system. Check for compatibility by applying a test patch of the recommended coating system, covering at least 2 to 3 square feet. Allow to dry one week before testing adhesion per ASTM D3359. If the coating system is incompatible, complete removal is required per ASTM D4259.
- F. No exterior painting should be done immediately after a rain, during foggy weather, when rain is predicted, or when the temperature is below 50°F, unless products are designed specifically for these conditions. On large expanses of metal siding, the air, surface and material temperatures must be 50°F or higher to use low temperature products.
- G. This schedule is not inclusive of all Sherwin-Williams products; other products and finishes are available.
- H. Not all products are compliant nationwide, visit related websites for CARB, OTC, SCAQMD for current VOC regulations.
 - CARB — <http://www.arb.ca.gov/coatings/coatingsrules.htm>
 - OTC — www.otcair.org
 - SCAQMD — <http://www.aqmd.gov/rules>
- I. Product names, logos, brands and other trademarks are the property of their respective trademark holders.
- J. Refer to the current MSDS/EDS for specific VOCs (calculated per 40 CFR 59.406). VOCs may vary by base and sheen.
- K. Coating Maintenance Manual: upon conclusion of the project, the Contractor or paint manufacture/supplier shall furnish a coating maintenance manual, such as Sherwin-Williams "Custodian Project Color and Product Information" report or equal. Manual shall include an Area Summary with finish schedule, Area Detail designating where each product/color/finish was used, product data pages, Material Safety Data Sheets, care and cleaning instructions, touch-up procedures, and color samples of each color and finish used.

Lobby / Common Area:

CMU — Concrete Masonry Units

Semi-Gloss Finish

- Primer:** [PrepRite® Block Filler](#), B25W25
1st coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series
2nd coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series

Semi-Gloss — High Performance Finish

- Primer:** [Loxon® Block Surfacers](#), A24W200
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Eg-Shel Finish

- Filler:** [PrepRite® Block Filler](#), B25W25
1st coat: [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series
2nd coat: [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series

Eg-Shel — High Performance Finish

- Primer:** [Loxon® Block Surfacers](#), A24W200
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Eg-Shel](#), K45 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Eg-Shel](#), K45 Series

Masonry and Concrete — Ceilings and Soffits

Flat Finish

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series
2nd coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series

Gypsum Board — Walls

Semi-Gloss Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series
2nd coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series

Semi-Gloss — High Performance Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Eg-Shel Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series
2nd coat: [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series

Eg-Shel — High Performance Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Eg-Shel](#), K45 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Eg-Shel](#), K45 Series

Lobby / Common Area (Cont.):

Gypsum Board — Ceilings and Soffits

Flat Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series
2nd coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series

Wood — Painted Doors, Frames, Trim and Chair Rails

Semi-Gloss Finish

- Primer:** [PrepRite® ProBlock® Latex Primer/Sealer](#) B51 Series
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate:

- Primer:** [PrepRite® ProBlock® Latex Primer/Sealer](#) B51 Series
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Wood — Stained Doors, Frames, Trim and Chair Rails

Stained Finish

- Stain:** [Minwax® 250 Interior Stain](#)
2nd coat: [Minwax® Water Based Polyurethane Varnish, Satin or Gloss](#)
3rd coat: [Minwax® Water Based Polyurethane Varnish, Satin or Gloss](#)

Ferrous Metal — Doors, Frames and Miscellaneous Metals

Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Ferrous Metal — High Performance Finish for Handrails

Eg-Shel or Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

Non-Ferrous Metal — Galvanized/Aluminum Surfaces

Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Lobby / Common Area (Cont.):

Non-Ferrous Metal — High Performance Finish for Handrails

Eg-Shel or Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

Food Area / Restroom / Corridor:

CMU — Concrete Masonry Units

Gloss — High Performance Finish

- Filler:** [Loxon® Block Surfacer](#), A24W200
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series

Semi-Gloss Finish

- Filler:** [Loxon® Block Surfacer](#), A24W200
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Eg-Shel Finish

- Filler:** [Loxon® Block Surfacer](#), A24W200
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Eg-Shel](#), K45 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Eg-Shel](#), K45 Series

Eg-Shel — High Performance Finish

- Filler:** [Loxon® Block Surfacer](#), A24W200
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series

Masonry and Concrete — Ceilings and Soffits

Flat Finish

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series
2nd coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series

Gypsum Board — Walls

Gloss — High Performance Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Gloss](#), B73-300 Series

Semi-Gloss Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Food Area / Restroom / Corridor (Cont.):

Eg-Shel Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Eg-Shel](#), K45 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Eg-Shel](#), K45 Series

Eg-Shel — High Performance Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-300 Series

Gypsum Board — Ceilings and Soffits

Flat Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series
2nd coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series

Ferrous Metal — Doors, Frames and Miscellaneous Metals

Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Ferrous Metal — High Performance Finish for Handrails

Eg-Shel or Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

Non-Ferrous Metal — Galvanized/Aluminum Surfaces

Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Non-Ferrous Metal — High Performance Finish for Handrails

Eg-Shel or Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

Cubicle / Office / Conference Room / Break Room:

Gypsum Board — Ceilings and Soffits

Flat Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series
2nd coat: [ProMar® 400 Zero VOC Interior Latex Flat](#), B30-4600 Series

Gypsum Board — Walls

Semi-Gloss Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series
2nd coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series

Eg-Shel Finish

- Primer:** [ProMar® 200 Zero VOC Latex Primer](#), B28W2600
1st coat: [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series
2nd coat: [ProMar® 200 Zero VOC Interior Latex Eg-Shel](#), B20-2600 Series

Ferrous Metal — Doors, Frames and Miscellaneous Metals

Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series
2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Ferrous Metal — High Performance Finish for Handrails

Eg-Shel or Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

Cubicle / Office / Conference Room / Break Room (Cont.):

Non-Ferrous Metal — Galvanized/Aluminum Surfaces

Semi-Gloss Finish

Primer: [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Alternate:

Primer: [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

1st coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

2nd coat: [Pro Industrial™ Pre-Catalyzed Waterbased Epoxy Semi-Gloss](#), K46 Series

Non-Ferrous Metal — High Performance Finish for Handrails

Eg-Shel or Gloss Finish

Primer: [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series

1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

Manufacturing / Warehouse / Distribution:

CMU — Concrete Masonry Unit Walls

Semi-Gloss Finish

- Primer:** [PrepRite® Block Filler](#) B25W25
1st coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series
2nd coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series

Eg-Shel or Semi-Gloss — High Performance Finish

- Primer:** [Loxon® Block Surfer](#), A24W200
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Semi-Gloss, B73-300 Series
2nd coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Semi-Gloss, B73-300 Series

Masonry Walls

Semi-Gloss Finish

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series
2nd coat: [ProMar® 200 Zero VOC Interior Latex Semi-Gloss](#), B31-2600 Series

Ferrous Ceiling Decking — Including Bar Joists

Flat, Eg-Shel, or Semi-Gloss Finish

- Primer:** [Pro Industrial Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Water Borne Acrylic Dryfall, Flat](#), B42-181 Series, Eg-Shel, Semi-Gloss, B42-80 Series
2nd coat: [Pro Industrial™ Water Borne Acrylic Dryfall, Flat](#), B42-181 Series, Eg-Shel, Semi-Gloss, B42-80 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Multi-Surface Acrylic Eg-Shel](#), B66-560 Series
2nd coat: [Pro Industrial™ Multi-Surface Acrylic Eg-Shel](#), B66-560 Series

Non-Ferrous Decking

Flat, Eg-Shel, or Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Waterborne Acrylic Dryfall, Flat](#), B42-181 Series, Eg-Shel, Semi-Gloss, B42-80 Series
2nd coat: [Pro Industrial™ Waterborne Acrylic Dryfall, Flat](#), B42-181 Series, Eg-Shel, Semi-Gloss, B42-80 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Multi-Surface Acrylic Eg-Shel](#), B66-560 Series
2nd coat: [Pro Industrial™ Multi-Surface Acrylic Eg-Shel](#), B66-560 Series

Ferrous Metal — Doors, Frames, and Miscellaneous Metals

Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Ferrous Metal — High Performance Finish for Handrails

Eg-Shel or Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310 Series
1st coat: [Pro Industrial™ Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series
2nd coat: [Pro Industrial Water Based Catalyzed Epoxy Eg-Shel](#), B73-360 Series or Gloss, B73-300 Series

Concrete Floors — Clear:

1st coat: [H&C® Wet Look Sealer](#)

2nd coat: [H&C® Wet Look Sealer](#)

Concrete Floors — Pigmented:

Light Duty (Foot Traffic)

1st coat: [ArmorSeal® Tread-Plex™](#)

2nd coat: [ArmorSeal® Tread-Plex™](#)

Medium/Heavy Duty (Kitchen Areas, Food Service, Restrooms, Labs, Warehouse, Corridors)

Gloss Finish

1st coat: [ArmorSeal® 8100 Finish](#) B70-8100 Series

2nd coat: [ArmorSeal® 8100 Finish](#) B70-8100 Series

Satin Finish

1st coat: [ArmorSeal® 8100 Finish](#) B70-8160 Series

2nd coat: [ArmorSeal® 8100 Finish](#) B70-8160 Series

Heavy Traffic Areas (Premium Performance)

1st coat: [ArmorSeal® 33 Epoxy Primer](#)

2nd coat: [ArmorSeal® 650 SL/RC](#)

Concrete Floors — Decorative:

Sherwin-Williams, offers a full line of patching materials, basecoats and high-performance floor finishes. Sherwin-Williams has a coating solution for most surfaces.

Please contact your local Sherwin-Williams representative for detailed information and specifications.

Warehouse/Distribution/Manufacturing Facility Exterior Paint Schedule

Specifier Notes — Topcoats:

a. **A-100® Exterior Latex** — A 100% acrylic formula that offers a durable, professional quality coating available in a Flat, Satin, Low-Sheen, and Gloss finishes.

b. **Loxon XP™ Masonry Coating** — Provides flexibility, durability, and weather resistance. This product will protect against wind-driven rain when used on tilt-up, precast, or poured-in-place concrete, CMU, and stucco. This may be applied to a surface with a pH of 6 to 13.

c. **Waterbased Acrolon™ 100 Urethane** — A two-component, waterbased, acrylic urethane enamel. It is designed for high performance protection with outstanding exterior gloss and color retention properties.

d. **Pro Industrial™ Acrylic Coating** — A single-component, light industrial, 100% acrylic coating that flows and levels to a smooth finish. Available in Eg-Shel, Semi-Gloss, and Gloss finishes.

e. **UltraCrete Textured Masonry Topcoat** — A 100% acrylic aggregate filled coating used to produce a textured finish on exterior surfaces.

Recommended Finishes:

Body: Flat or Satin (unless otherwise noted)
Trim: Semi-Gloss or Gloss Finish (unless otherwise noted)

Warehouse/Distribution/Manufacturing Facility Exterior Paint Schedule

Exterior Tilt-Up Concrete / Masonry Areas (Smooth):

Satin Finish

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [A-100® Exterior Latex Satin](#), A82 Series
2nd coat: [A-100® Exterior Latex Satin](#), A82 Series

Flat Finish

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [A-100® Exterior Latex Flat](#), A6 Series
2nd coat: [A-100® Exterior Latex Flat](#), A6 Series

Textured Finish

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300 (On high pH surfaces, 9 or greater, use primer.)
1st coat: [UltraCrete Textured Masonry Topcoat Fine, Medium, Extra Coarse](#), A44-800 Series
2nd coat: Optional — [UltraCrete Textured Masonry Topcoat Fine, Medium, Extra Coarse](#), A44-800 Series

Flat Finish — High Build

- Primer:** [Loxon XP™ Waterproofing System](#), A24-1400 Series
1st coat: [Loxon XP™ Waterproofing System](#), A24-1400 Series

Exterior CMU & Block Areas (Porous):

Satin Finish

- Filler:** [Loxon® Block Surfer](#), A24W200
1st coat: [ConFlex XL™ High Build Smooth](#), A5-400 Series
2nd coat: [ConFlex XL™ High Build Smooth](#), A5-400 Series
(A total dry film thickness of 12 – 15 mils and a surface of 10 or less pinholes per square foot is required for a waterproofing system)

Flat Finish — High Build

- 1st coat:** [Loxon XP™ Waterproofing System](#), A24-1400 Series
2nd coat: [Loxon XP™ Waterproofing System](#), A24-1400 Series

Exterior Ferrous Metals:

High Performance Finish — Doors, Canopies, Handrails, Bollards

Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310
1st coat: [Pro Industrial™ Urethane Alkyd Enamel](#), B54-150 Series
2nd coat: [Pro Industrial™ Urethane Alkyd Enamel](#), B54-150 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310
1st coat: [Waterbased Acrolon® 100 Polyurethane Gloss](#), B65-720 Series
2nd coat: [Waterbased Acrolon® 100 Polyurethane Gloss](#), B65-720 Series

Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Exterior Non-Ferrous Metals:

High Performance Finish — Doors, Canopies, Handrails, Bollards

Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310
1st coat: [Pro Industrial™ Urethane Alkyd Enamel](#), B54-150 Series
2nd coat: [Pro Industrial™ Urethane Alkyd Enamel](#), B54-150 Series

Alternate:

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310
1st coat: [Waterbased Acrolon® 100 Polyurethane Gloss](#), B65-720 Series
2nd coat: [Waterbased Acrolon® 100 Polyurethane Gloss](#), B65-720 Series

Semi-Gloss Finish

- Primer:** [Pro Industrial™ Pro-Cryl® Universal Primer](#), B66-310
1st coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series
2nd coat: [Pro Industrial™ Acrylic Semi-Gloss](#), B66-650 Series

Exterior Wood:

Gloss Finish

- Primer:** [Exterior Latex Wood Primer](#), B42W8041
1st coat: [A-100® Exterior Latex Gloss](#), A8 Series
2nd coat: [A-100® Exterior Latex Gloss](#), A8 Series

Satin Finish

- Primer:** [Exterior Latex Wood Primer](#), B42W8041
1st coat: [A-100® Exterior Latex Satin](#), A82 Series
2nd coat: [A-100® Exterior Latex Satin](#), A82 Series

Exterior Plaster / Stucco:

Satin Finish

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [A-100® Exterior Latex Satin](#), A82 Series
2nd coat: [A-100® Exterior Latex Satin](#), A82 Series

Flat Finish

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [A-100® Exterior Latex Flat](#), A6 Series
2nd coat: [A-100® Exterior Latex Flat](#), A6 Series

Flat Finish — High Build

- Primer:** [Loxon XP™ Waterproofing Coating](#), A24-1400 Series
1st coat: [Loxon XP™ Waterproofing Coating](#), A24-1400 Series

Satin Finish — High Build

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [ConFlex XL™ High Build Smooth](#), A5-400 Series
2nd coat: [ConFlex XL™ High Build Smooth](#), A5-400 Series

Textured Finish — High Build

- Primer:** [Loxon® Concrete & Masonry Primer Sealer](#), A24W8300
1st coat: [UltraCrete Textured Masonry Topcoat, Fine, Medium, Extra Coarse](#), A44-800 Series
2nd coat: [UltraCrete Textured Masonry Topcoat, Fine, Medium, Extra Coarse](#), A44-800 Series





©2015 The Sherwin-Williams Company