

1 Article

# 2 Over-pumping groundwater in northern Jordan, the 3 case of Irbid governorate: a conceptual model to 4 analyze the effects of urbanization and agricultural 5 activities on the groundwater level and salinity

6 Taleb Odeh<sup>1</sup> Alsharifa Hind Mohammad<sup>2</sup> Hussam Hussein<sup>3,4\*</sup> Mamoon Ismail<sup>5</sup> Thair Almomani<sup>6</sup>

7 1 The Hashemite University - Prince Al Hassan Bin Talal Faculty of arid lands - Zarqa 13133 Jordan

8 2 The University of Jordan - Water, Energy and Environment center - Amman 11942 Jordan

9 3 International Agricultural Policy and Environmental Governance, University of Kassel, Steinstrasse 19,  
10 Witzenhausen, 37213, Germany

11 4 Water Security Research Centre, School of International Development, University of East Anglia (UEA),  
12 Norwich, NR4 7TJ, UK

13 5 Water Authority of Jordan - Groundwater Basins Protection Directorate – Amman 11183 Jordan

14 6 Ministry of Water and Irrigation of Jordan - Division of Water Strategies - P.O.Box 2412-11181 Amman  
15 Jordan

16 \* Correspondence: email: hh.hussam.hussein@gmail.com

17 **Abstract:** Irbid governorate has the highest population density in Jordan and most of its water  
18 demand is supplied by groundwater. Both natural population growth and waves of migrations  
19 increased the number of its inhabitants during the last forty years. The increased number of  
20 inhabitant resulted in extending the urban and agricultural areas. Also, the demand for domestic  
21 water uses increased as a result of the increased number of inhabitant, while the extended  
22 agricultural area meant increasing the water demand for irrigation. Due to the expansion of urban  
23 areas, water was required for the construction sector. Most of the water resources needed for these  
24 sectors came and comes from groundwater resources. Nowadays, the increased water demand is  
25 putting a strain on the groundwater resources, which are currently over-exploited beyond their  
26 safe-yield. As a result of the continuous pumping, the groundwater level is decreasing rapidly and  
27 the salinity increasing gradually. This paper presents a conceptual model we have produced to  
28 measure this process through an integrated approach of remote sensing and Geographic  
29 Information Systems (GIS).

30 **Keywords:** Conceptual modeling; groundwater resources; Jordan; water demands; remote sensing;  
31 GIS

32

## 33 Introduction

34 Literature on water resources in Jordan focused on hydrological approaches and engineering  
35 solutions to water scarcity, with regional attention to the Jordan Valley, and to the Amman  
36 governorate. Extensive literature has been published on issues related to the water crisis in Jordan,  
37 which makes it impossible to fairly review within a brief literature review. In particular, Jordan is said  
38 to be among the most water scarce countries in the world, facing serious problems related to water shortages,  
39 which negatively affect its entire development [1-5]. Recent research showed that the Jordanian government has  
40 been exploring several solutions to increase the water supply in the country, from building the Wahda Dam, the  
41 Disi Canal project recently completed, and supporting the construction of the Red Sea – Dead Sea Canal [6-8].  
42 Literature on water resources and water policies in Jordan has investigated mainly the cases of Amman  
43 governorate- where most of the population resides – and of the agricultural activities in the Jordan Valley

44 [9-11]. Previous research has adopted geospatial techniques for improved water management in the  
45 country [12]; Withheritrong et al., [13] analysed estimation of the effect of soil texture on  
46 nitrate-nitrogen content in groundwater using optical remote sensing – although not for the case of  
47 Jordan -; Dogrui et al. [14] analysed groundwater modeling in support of water resources  
48 management and planning under complex climate, regulatory, and economic stresses, although not  
49 specifically in the case of Jordan; and Mohammad et al. [15] recently investigated the impact of  
50 droughts in the Yarmouk Basin, in Jordan, by monitoring the droughts through meteorological and  
51 hydrological drought indices. Nevertheless, what emerges from the review of the relevant literature  
52 is that little research has been done on the impacts of the evolving human activities – specifically of  
53 agricultural and urban activities – on the groundwater resources in the governorate of Irbid. This  
54 paper aims to make a novel contribution by presenting a conceptual model to measuring the process  
55 of human urbanization and increased agricultural activities over time according to an integrated  
56 approach of remote sensing and Geographic Information Systems (GIS) applied to the Irbid  
57 Governorate.

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79 **Study area and background information**

80 Jordan has an area of about 89.34 Km<sup>2</sup> that is divided into 12 governorates, and Irbid governorate  
 81 has an area of about 1.572 km<sup>2</sup> (Fig. 1). As a result of the tectonic events and geomorphological  
 82 processes, Irbid governorate has high relief topography [16] (Fig. 2). Because of the variations of  
 83 elevations, there are different rainfall patterns in the region, as showed in Figure 3, [17-18]. Irbid  
 84 governorate has the second biggest population in the country, after the capital city Amman,  
 85 however Irbid has the highest population density in Jordan [19].

86

87

88

89

90

91

92

93

94

95

96

97

98


99

100

101

102

103




104

105

106

107

Fig. 1: Study area location so called Irbid governorate. It has a border with Syria, west bank and Israel. It has the city of Irbid that has the second biggest population in Jordan after the capital Amman.




108

109

110

**Fig. 2:** The topography of the study area. The western part is the lowest elevation that is a part from the Jordan valley. The southern part has the highest elevation that is a part form Ajloun mountains.






**Fig. 3:** Rainfall quantity spatial distributions of the study area (average of 40 years 1984 – 2014). Meteorological Department 2014 open data source. The amount of rainfall is over the highest topographical elevation at Ajloun mountains.

115 Irbid governorate is located in the north-western part of Jordan. Two major rivers pass through  
 116 the governorate, Al Yarmouk River in the north and the Jordan River in the west; nevertheless the  
 117 major source of water supply is its groundwater resources [3; 4; 15; 17]. This is because the discharges  
 118 of the two mentioned rivers is limited (Al Yarmouk River 14.5 m<sup>3</sup>/s, Jordan River 16 m<sup>3</sup>/s) and  
 119 because they are both of transboundary nature, hence Jordan needs to respect the bilateral treaties  
 120 signed about the uses of these rivers [6; 15].

121 The groundwater of Irbid governorate comes mainly from a hydrogeological basin called Al  
 122 Yarmouk. It is shared with Syria and has an area of about 1426 Km<sup>2</sup> [16; 20]. The basin is composed  
 123 mainly from shallow unconfined unsaturated aquifers. The rock matrix of the aquifers is mainly of  
 124 tertiary chalks and limestone and basaltic rocks [16]. However, alluvial deposits are found in the  
 125 wadis especially in the west of the basin. The average hydraulic conductivity of the basin varies from  
 126  $1 \times 10^{-4}$  to  $1 \times 10^{-6}$  m/s. The maximum groundwater level is in the south of the study area and reach up  
 127 to 1000 m absl. While the minimum the groundwater level is the eastern side of the study area and

128 reach down to about – 239 meter absl. [6; 15]. The groundwater flow from the south to north mostly  
 129 but in the eastern side of the study it moves from east to west. The average groundwater recharge is  
 130 about 8% to 10% from the annual rainfall and the safe yield of the basin is estimated to be 40 Million  
 131 Cubic Meter (MCM) [21].

132 Irbid governorate received several migrations waves during recent history [22] (Fig. 4). The  
 133 first wave was in 1948 after the first Arab–Israeli war, when Palestinian refugees came to Irbid  
 134 governorate. The second wave was after the Arab-Israeli Six Days War in 1967. After the war  
 135 thousands of Palestinian refugees came to Jordan, settling also in the Irbid governorate. Moreover,  
 136 other two migration waves came after the first and second gulf war in 1991 and 2003 respectively.  
 137 Hundred thousands of Jordanians and Palestinians moved from Kuwait to Jordan following the first  
 138 Gulf War. In 2011 the civil war in Syria started, and about half a million Syrian refugees came to  
 139 Irbid governorate. Furthermore, Irbid governorate with 3.2% has one of the highest population  
 140 growth rates in the region. Both the increased number of refugees and the natural high population  
 141 growth rate play a major role for increasing the number of inhabitants rapidly in Irbid governorate  
 142 [22; 19]



Note: 85% of Jordan's population lives in cities.

Source: FAO Aquastat (2014).

143

144 **Fig. 4:** The population growth in Jordan [23]. The water availability per person is decreasing while the  
 145 number of the inhabitant is increasing.

146 The first and main reason of extension of the urban area is the increases population [24].  
 147 Naturally, the increased number of habitant and the extended urbanized area would consume more  
 148 water in order to supply the drinking water and construction water respectively [25]; nevertheless,  
 149 it has been shown in recent literature that most water supply in Jordan goes to the agricultural sector  
 150 rather than for domestic uses [4; 10]. Nevertheless, population growth and extension of the urban  
 151 area in Irbid governorate had an impact on the groundwater level and salinity. This impact was due  
 152 to increasing groundwater abstraction way beyond the safe yield. This study aims at shading light  
 153 on this exact relationship.

154

155

**156 Methodology**

157 The integrated approach Remote Sensing (RS) and the Geographic Information Systems (GIS) have  
158 been recently widely used in order to analyze, store, and display land surface data [26; 27].  
159 However, RS could produce the land surface data of the land cover in form of satellite images, but  
160 those images have to be classified in order to generate the land cover classes [28]. The images and  
161 their classifications could be stored in form of raster, which is a major type of GIS data (geo-data).  
162 GIS is a useful tool for spatial analyzing raster data. Hence, RS and GIS are integrated in a useful  
163 approach for land surface data generating [26-29].

164

165 Landsat represents the world's longest continuously acquired collection of space-based  
166 moderate-resolution land remote sensing data. Four decades of imagery provides a unique data  
167 resource for scientists in deferent fields. These data are in form of raster data that is crucial to GIS  
168 analysis. It has capacity to provide repetitive and synoptic observations of the land surface that  
169 makes it powerful tool in giving information on how land cover changes over a span of time. We  
170 used Land sat 5 images for the years of 1984, 1994 and 2004 since it has data record for these years  
171 while for the year of 2014 Landsat 7 image was used. Any Landsat image has at least 7 spectral  
172 bands with a spatial resolution of 30 meters for Bands 1-5, and 7. For our classifications we used the  
173 visible bands that have a resolution of thirty meter and available in for all the landsat images.  
174 However, all the landsat images that were used in our study were downloaded from the landsat  
175 data access (<https://landsat.usgs.gov/landsat-data-access>).

176 ENVI 6 is an image analysis software that is used by GIS professionals, remote sensing  
177 scientists, and image analysts to extract meaningful information about the land surface class from  
178 the satellite Images [26-27]. ENVI 6 software have a many automated data analysis tools that could  
179 access spatial algorithms to rapidly, swiftly, and precisely analyze imagery, such as estimate image  
180 geostatistics, measure area and distance features and image supervised classification [26]. Therefore,  
181 we used ENVI 6 software as a remote sensing software. The objective from that was to carry out a  
182 supervised classification for Landsat images in order to understand the classes of the land surface.  
183 However, there are four major methods for supervised classification in ENVI 6 software: Maximum  
184 Likelihood, Minimum Distance, Mahalanobis Distance and Spectral Angle Mapper. The minimum  
185 distance method gave the best overall accuracy (Tab. 1) therefore we consider it for the classification.  
186 Parts of the study area has remote sensing investigations by other studies such Al-Kofahi et al 2017  
187 [30] and Sawalhah [31] were they explained and discussed in details that approach.

188 However, we categorize the land surface area into only four classes, which have a major  
189 influence on the groundwater recharge, as follows: A) Soil units, B) Rock unit, C) Urban land and D)  
190 agricultural land. However, we carry out the supervised classification, for the visible bands, to  
191 generate these four land cover classes for the Landsat 7 of the time periods of 1984, 1994, 2004 and  
192 2014. These time periods are on constancy with the time periods of the hdrogeological data that we  
193 would compare the land surface classes changes detections with it (Fig. 5). The validation of the  
194 classifications was according to filed work visits for the landsat image of 2014 and Google earths  
195 imageryes for 2004, 1994 and 1984 landsat images.

196

197

198

199

200

201

202

203

204

205


206  
207  
208

Tab. 1: Confusion matrix table. It represents the accuracy assessment for the classifying process of landsat images.

			Reference data				Summations	Users' accuracy
Irbid governorate Land sat Image			Soil units	Urban land	Agricultural land	Rock unit		
2014	Classifications	Soil units	30	1	9	2	42	0.71
		Urban land	3	28	2	5	38	0.74
		Agricultural land	5	3	27	2	37	0.73
		Rock unit	2	8	2	31	43	0.72
	Summations		40	40	40	40	160	
	Producers' accuracy		0.75	0.70	0.68	0.78		0.73
2004	Classifications	Soil units	31	1	6	3	41	0.76
		Urban land	2	29	1	4	36	0.81
		Agricultural land	4	1	32	3	40	0.80
		Rock unit	3	8	1	30	42	0.71
	Summations		40	40	40	40	160	
	Producers' accuracy		0.78	0.73	0.80	0.75		0.76
1994	Classifications	Soil units	32	2	2	1	37	0.86
		Urban land	1	28	1	3	33	0.85
		Agricultural land	3	1	35	1	40	0.88
		Rock unit	6	7	1	33	47	0.70
	Summations		40	40	40	40	160	
	Producers' accuracy		0.80	0.70	0.88	0.83		0.80
1984	Classifications	Soil units	33	1	3	1	38	0.87
		Urban land	1	30	1	4	36	0.83
		Agricultural land	8	1	34	1	44	0.77
		Rock unit	1	8	1	34	44	0.77
	Summations		40	40	40	40	160	
	Producers' accuracy		0.83	0.75	0.85	0.85		0.82

209  
210  
211  
212





225 **Fig. 5: A flow chart for a conceptual model of land cover – groundwater level changes detection.**  
 226 comparing groundwater level and land cover class. Both of the groundwater level and the land cover  
 227 class are in form of raster.

228 The supervised classifications by minimum distance method of all our satellite images has  
 229 overall accuracy greater than 70% that is applicable according to Smith et al 2002 [32]. Thematic  
 230 maps are one of the most common tools that could be used in order to understand the spatial  
 231 distributions of specific phenomena [28]. GIS is a powerful tool to achieve that. ArcGIS 10.2 software  
 232 with its spatial analyst extension is widely used currently for thematic map generating because of its  
 233 useful interface [33]. Therefore, we used it to generate a thematic map for the groundwater level  
 234 during time periods of the available groundwater data of Ministry of Water and Irrigation (MWI) in  
 235 Jordan which are: 1984, 1994, 2004 and 2014.


236 However, the first step was converting the excel data of the groundwater level of the wells and  
 237 spring elevations and their coordinates into a vector – points (shapefile namely) by ArcGIS 10.2. The  
 238 spatial analyst extension in ArcGIS 10.3 could interpolate groundwater levels into thematic maps by  
 239 the Inverse Distance Weighted (IDW) method. The IDW method includes an estimated weighted  
 240 average method where the weights of the measured data points,  $Z(u_i)$ ,  $i = 1, 2, \dots, M$ , is set inversely  
 241 proportional to their distances,  $h_i$ , from an interpolated unmeasured point,  $Z(u_x)$ . It could be  
 242 calculated as follow:

243

$$Z(ux) = \frac{\sum_{i=1}^M \left[ \frac{1}{h_i^p} \times Z(u_i) \right]}{\sum_{i=1}^M \frac{1}{h_i^p}} \quad (1)$$

244  
 245  
 246  
 247  
 248  
 249  
 250  
 251  
 252  
 253  
 254  
 255  
 256  
 257  
 258  
 259  
 260  
 261  
 262  
 263  
 264  
 265  
 266  
 267  
 268  
 269  
 270  
 271  
 272  
 273  
 274  
 275  
 276  
 277  
 278  
 279  
 280  
 281  
 282  
 283  
 284  
 285  
 286

The values that is in gray shadow represents the overall classification accuracy. where  $p > 0$  is a power parameter. However, the IDW method has several advantages for interpolation such as: could calculate changes in terrain such as cliffs and faults line in addition to it could increase or decrease the number of the sample points to influence cell values [34]. Therefore, we used it as a method for interpolate the thematic maps of the groundwater levels. For that purpose we used 76 hydrogeological points (Fig. 6) that are in and around our case study. The hydrogeological points are the available wells and spring that have hydrogeological record in the ministry of water and irrigation. However, in general, because of data discontinuity/scarcity, not all the wells and springs have a full hydrogeological record [35]. We chose four time periods for interpolation. These time periods are near to the time periods of the migration waves in order to evaluate how the increasing in the inhabitant effects the groundwater level and hence the groundwater salinity. These time periods are: 19984, 1994, 2004 and 2014. They are the exact time periods of the classified Landsat 7 images in order to compare the land classes detection with the groundwater level changes.



287

288 **Fig. 6:** Available hydrogeological points in the study area. The groundwater levels of these points  
 289 were interpolated to generate a conceptual model for the groundwater level spatial changes. Not all  
 290 the wells have complete data record about the water level and salinity for forty years therefore tow  
 291 well only were selected to detect the changes of water level and salinity.

292

293

294

295

296


297

298 **Results and discussion**

299 Figure 7 shows that the land cover of Irbid governorate was changing unregularly during the last  
 300 forty years. It also shows that the urbanized area was growing rapidly during the same time, as a  
 301 result of the growing population [24; 19]. It also shows that the agricultural area decreased in the  
 302 first ten years (1984 – 1994). This is due to the fact that youth whom were working in the agricultural  
 303 sector started moving toward the main cities to take up jobs in the governmental sector, which was  
 304 expanding and employing in that time period [36; 22; 19]. However, the following ten years  
 305 (1994-2014) the agricultural area started to increase because the governmental sector was almost

306 saturated, stopping expanding and hiring new people, and the people therefore preferred moving  
 307 toward the agricultural jobs again [22; 19]. In this period many businessmen were investing in land  
 308 and agribusinesses in this part of the country, expanding agricultural activities and job opportunities  
 309 in the area [4].

310  
 311  
 312  
 313



314

315 **Fig. 7:** Land cover changes detections of the study area. During the last forty years the urbanized area  
 316 were extended rapidly. Land sat 5 images were used for the years of 1984, 1994 and 2004 while for  
 317 the year of 2014 Landsat 7 image was used to generate a conceptual model for the land cover spatial  
 318 changes.


319 From a geological perspective, the area of the soil is associated with the area of agricultural land  
 320 [37]. When the area of the agricultural land decreased in the first ten year the area of the soil  
 321 increased [37; 38]. Moreover, in the following thirty years people started moving back toward the  
 322 agricultural activity, therefore, the agricultural land area increased [18; 19; 22].

323 The area of rock unit was decreasing during the first thirty years since people prefer to  
 324 construct the basement of houses, which is the major part of the urbanized area, on that unit in order  
 325 to reduce the cost of construction by not digging the soil [38; 39; 19]. The houses basements have to  
 326 be on rock layer so they do not crack during the winter as a result of soil liquefaction [34]. However,  
 327 in the last ten years the rock unit shows a slight increase up to 1% as a result of the soil erosion that  
 328 increased in the last 10 years [33].

329 Figure 8 shows the groundwater level spatial distributions of the study area. It shows where the  
 330 groundwater level changed as a result of the land cover changes during the last forty years.  
 331 However, land cover effects the groundwater level in two ways: 1) Reducing the groundwater

332 recharge by increasing the runoff water that is increasing urban area span and/or 2) Consuming  
 333 more groundwater in order to meet the high demands for irrigation and drinking purposes when  
 334 the agricultural land extended and the inhabitant increased respectively [40]. Both these ways  
 335 impacted the spatial distributions of groundwater level on the study area but the effects were not  
 336 spatially homogeneous.

337



338

339 **Fig. 8: The conceptual model of the groundwater level changes spatial detections of thirty years**  
 340 **duration.** In the first ten years (1984 – 1994) the groundwater level was rising in the north west of the  
 341 study area. After 1994 the groundwater level decrease in the same area as a result of the extended  
 342 urbanization.

343


344 From 1984 to 1994 the groundwater level increased in the north and northeast part of the study  
 345 area as a result of the decrease in agricultural activities during that time period, which meant  
 346 decreasing in pumped irrigated water [17]. However, in the south-eastern part of the study area a  
 347 zone of groundwater over-pumping was generated as result of heavy groundwater mining to  
 348 supply the increased number of inhabitants in that area, which saw a strong increase in  
 349 urbanization.

350 From 1994 to 2004 the groundwater depletion strongly impacted the north and northwestern  
 351 part of the study area as a result of the extending agricultural and urbanized area. Limestone




352 sinkholes started to be an obvious landscape phenomenon in that area as a result of the groundwater  
 353 depletion [41; 30]. However, the southern part of the study area has the highest elevation and  
 354 received the highest amount of rainfall so it has the highest amount of groundwater recharge.

355 From 2004 to 2014 the groundwater depletion impacted the east and the southeastern part of  
 356 the study area since the urbanization extended more intensively and the population increased as a  
 357 result of the latest wave of migration [19; 22] (Fig. 9). Hence, it is clear that groundwater depletion is  
 358 associated with the land cover detection in the study area.




359  
 360 **Fig. 9:** Population growth and Groundwater pumping increasing in Irbid governorate. They are both  
 361 in Exponential increasing.

362 The available hydrogeological data record of the study area received from the MWI were also  
 363 examined and this study found that only two wells have data about the groundwater level and  
 364 salinity for forty years. The objective of that was to correlate the decreasing level of groundwater  
 365 with its increasing salinity. Previous studies confirmed that in Jordan salinity increases with  
 366 groundwater level decreasing [42]. This is due to the fact that deeper waters have more retention  
 367 times to accumulate dissolved salts than the higher water. Figure 10 shows that the groundwater



368 level in the  
 369 **Fig. 10:** Groundwater level changes (A and D) and groundwater salinity changes (B and C) in the two  
 370 selected wells. Kufir Asad well locates in the north of the study area while Wadi El Yabis well locates  
 371 in the south of the study area.

372 northern part of the study area decreased more rapidly than the groundwater level in the southern  
 373 part and that the salinity of the groundwater in the north was increasing faster than in the south.



374 Figure 11 shows our conceptual model in form of flow chart. It indicates that the repaid increased

375 Fig. 11: A conceptual model for the mechanism of the increased inhabitants effects on groundwater.  
 376 When the groundwater level is decreased the groundwater salinity is increased and sinkhole-prone  
 377 area would increase too.

378 The number of inhabitants increased the groundwater demands which generate more groundwater  
 379 pumping. The annual groundwater pumping is much more than the annual ground recharge  
 380 therefore groundwater level decrease characterize a typical case of over-pumping. Our model  
 381 indicates that that the over-pumping in our case study doesn't only increase the groundwater  
 382 salinity but it creates sinkhole prone area.

383

384

### 385 Conclusions

386 There is a strong positive correlation between the groundwater depletion and extending  
 387 urbanization and agricultural activities. Unsurprisingly, population growth is linked to extending  
 388 urbanization and urban areas, as well as agricultural activities and agricultural investments.  
 389 Drilling pumping wells has to consider the zonation of surface rainfall and the zonation of  
 390 groundwater recharge. The area of highest amount of rainfall is usually the area of highest amount  
 391 of groundwater recharge and it is more resistant and resilient to groundwater depletion. This study  
 392 also found a positive correlation between the groundwater level and groundwater salinity, therefore  
 393 population growth, urbanization, and agricultural activities do not threat only groundwater  
 394 quantity (when over-pumped, such as in the case of northern Jordan), but also groundwater quality.  
 395

396 In the case of limestone aquifers, sinkholes are natural risks that impact the area of groundwater  
 397 depletion zone. In the study area, sinkholes and the groundwater zones are extended rapidly and  
 398 intensively where the groundwater depletion is found. Sinkholes have a direct negative impact on  
 399 the urbanization areas because of its ability to destroy houses, buildings, and roads. Thus, the effects  
 400 of groundwater depletion are not only negative on the water quality but also on the urban safety too.

401  
 402 Conceptual hydrogeological models are very important in order to conduct a sustainable  
 403 management of the groundwater resources. They describe the elements of the water conflicts and  
 404 prerequisite for solid numerical groundwater models. Our conceptual model for the water crisis in  
 405 Irbid governorate indicates that groundwater is the major water resource and its abstraction  
 406 quantities is rapidly increased in order to supply the increased number of inhabitants and their  
 407 activities. However, our model indicates the abstraction rate is much more than the groundwater  
 408 recharge rate, therefore the groundwater level decrease. We do recommend a numerical  
 409 groundwater modelling for the study area in order to determine the optimized quantity of  
 410 groundwater pumping. Furthermore, alternative water resources in the study area must be  
 411 generated in order to reduce the pressure on the groundwater resource.

412  
 413

414 **Acknowledgement:** The authors are grateful to the Ministry of Water and Irrigation (MWI) for providing  
 415 the groundwater data used in this paper.

#### 416 References

- 417 [1] Jasem A, Raggad M (2010) Assessing groundwater vulnerability in Azraq basin area by a modified  
 418 DRASTIC index J. Water Resource and Protection, 2010, 2, 944-951doi:  
 419 <https://doi.org/10.4236/jwarp.2010.211112> (<http://www.SciRP.org/journal/jwarp>)
- 420 [2] Mohammad AH, Almomani T, Alhejoj I (2015) Groundwater vulnerability for the surface outcropping  
 421 aquifers in Jordan. J Environ Prot 6: 250–258. <https://doi.org/10.4236/jep.2015.63025>
- 422 [3] Hussein, H. (2018a), Yarmouk, Jordan, and Disi basins: Examining the impact of the discourse of water  
 423 scarcity in Jordan on transboundary water governance. *Mediterranean Politics*, 1-21, DOI:  
 424 10.1080/13629395.2017.1418941
- 425 [4] Hussein, H. (2018b), Tomatoes, tribes, bananas, and businessmen: An analysis of the shadow state and of  
 426 the politics of water in Jordan. *Environmental Science & Policy*, 84, 170-176, DOI:  
 427 10.1016/j.envsci.2018.03.018
- 428 [5] Hussein, H. (2018c), Lifting the veil: Unpacking the discourse of water scarcity in Jordan. *Environmental*  
 429 *Science & Policy*, 89, 385-392.
- 430 [6] Hussein, H. (2017a), Whose ‘reality’? Discourses and hydropolitics along the Yarmouk  
 431 River. *Contemporary Levant*, 2 (2), 103-115, DOI:[10.1080/20581831.2017.1379493](https://doi.org/10.1080/20581831.2017.1379493)
- 432 [7] Hussein, H. (2017b), Politics of the Dead Sea canal: a historical review of the evolving discourses, interests,  
 433 and plans. *Water Int* 42(5):527– 542. <https://doi.org/10.1080/02508060.2017.1344817>
- 434 [8] Hussein H. (2017c) A critique of water scarcity discourses in educational policy and textbooks in Jordan. *J*  
 435 *Environ Educ* 1–12. <https://doi.org/10.1080/00958964.2017.1373620>
- 436 [9] Haddadin MJ (Ed.). (2006). Water resources in Jordan: evolving policies for development, the  
 437 environment, and conflict resolution. Resources for the Future
- 438 [10] Hussein, H. (2016). An analysis of the discourse of water scarcity and hydropolitical dynamics in the case  
 439 of Jordan (Doctoral dissertation, University of East Anglia).
- 440 [11] Salameh, E., Shteivi, M., & Al Raggad, M. (2018). *Water Resources of Jordan: Political, Social and Economic*  
 441 *Implications of Scarce Water Resources* (Vol. 1). Springer.
- 442 [12] Al-Bakri, J. T., Shawash, S., Ghanim, A., & Abdelkhaleq, R. (2016). Geospatial techniques for improved  
 443 water management in Jordan. *Water*, 8(4), 132.
- 444 [13] Witheetrirong, Y., Tripathi, N. K., Tipdecho, T., & Parkpian, P. (2011). Estimation of the effect of soil  
 445 texture on nitrate-nitrogen content in groundwater using optical remote sensing. *International journal of*  
 446 *environmental research and public health*, 8(8), 3416-3436.
- 447 [14] Dogrul, E. C., Brush, C. F., & Kadir, T. N. (2016). Groundwater modeling in support of water resources  
 448 management and planning under complex climate, regulatory, and economic stresses. *Water*, 8(12), 592.

- 449 [15] Mohammad, A. H., Jung, H. C., Odeh, T., Bhuiyan, C., & Hussein, H. (2018). Understanding the impact of  
450 droughts in the Yarmouk Basin, Jordan: monitoring droughts through meteorological and hydrological  
451 drought indices. *Arabian Journal of Geosciences*, 11(5), 103.
- 452 [16] Bender F (1974) Geology of Jordan. Contribution of the regional geology of the earth. Borntraeger, Berlin
- 453 [17] Salameh E, Bannayan H (1993) Water Resources of Jordan—Present Status and Future Potentials. Friedrich  
454 Ebert Stiftung, Amman, p183.
- 455 [18] Moshrik H.R., Abu-Allaban M, Al-Shayeb A. (2009) Climate change in Jordan: A comprehensive  
456 examination approach. *Am. J. Environ. Sci.* 5: 58–68.
- 457 [19] Department of Statistics (2014) Statistical Yearbook; Government publication: Amman, Jordan, 2014; p.  
458 200.
- 459 [20] Abu-Jaber N, Kimberley M, Cavaroc V (1989) Mesozoic-Palaeogene basin development within the Eastern  
460 Mediterranean borderland. *J. Petrol. Geol.* 4: 419–436.
- 461 [21] Ministry of water and irrigation 2017 open data source.
- 462 [22] Perdew L (2014) Understanding Jordan Today; Mitchell Lane Publishers, Inc.: Newark, DE, USA, pp. 17–  
463 18.
- 464 [23] FAO Food and Agriculture Organization of the United Nations (2014) open data source. ((this reference  
465 for figure 4))
- 466 [24] Butler D, Davies J (2000) Urban Drainage. Spon Press, USA, p 483.
- 467 [25] Stephenson D (2003) Water resources management. Taylor and Francis, The Netherlands, p 323.
- 468 [26] Saraf K, Choudhury R, Roy B, Sarma B, Vijay S, Choudhury S (2004) GIS based surface hydrological  
469 modelling in identification of groundwater recharge zones. *Int J Remote Sens* 25:5759–5770.
- 470 [27] Odeh T, Rödiger T, Geyer S, Schirmer M (2015) Hydrological modelling of a heterogeneous catchment  
471 using an integrated approach of remote sensing, a geographic information system and hydrologic  
472 response units: the case study of Wadi Zerka Ma'in catchment area, north east of the Dead Sea. *Environ*  
473 *Earth Sci* 73:3309–3326.
- 474 [28] Chou Y (1997) Exploring Spatial Analysis in GIS; Onword Press: New York, NY, USA, p. 500.
- 475 [29] Berndtsson R, Larson M (1987) Spatial variability of infiltration in a semi-arid environment. *J Hydrol*  
476 90:117–133.
- 477 [30] Al-Kofahi S , Jamhawi M, Hajahjah Z, (2017) Investigating the current status of geospatial data and urban  
478 growth indicators in Jordan and Irbid municipality: implications for urban and environmental planning.  
479 *Environment, Development and Sustainability Journal*. <https://doi.org/10.1007/s10668-017-9923-y>.
- 480 [31] Sawalhah M., Al-Kofahi S, Othman Y, Andres F. Cibils (2018) Assessing rangeland cover conversion in  
481 Jordan after the Arab spring using a remote sensing approach, *Journal of Arid Environments* 157:97-102.
- 482 [32] Smith A, Wooster M, Powell A, Usher D (2002) Texture based feature extraction: application to burn scar  
483 detection in Earth observation satellite sensor imagery. *Int. J. Rem. Sens.* 23:1733–1739.
- 484 [33] Odeh T, Boulad N, Abed O, Abu Yahya A, Khries N, Abu-Jaber N 2017 The Influence of Geology on  
485 Landscape Typology in Jordan: Theoretical Understanding and Planning Implications. *Land* 6: 51.
- 486 [34] Wang Y , Akeju O, Zhao T (2017) Interpolation of spatially varying but sparsely measured geo-data:  
487 A comparative study. *Engineering Geology* 231: 200–2017.
- 488 [35] Wu Y, Wang W, Toll M, Alkhoury W, Sauter M, Kolditz O (2011) Development of a 3D groundwater  
489 model based on scarce data: the Wadi Kafrein catchment/Jordan. *Environ Earth Sci* 64: 771-785.
- 490 [36] US Department of agriculture (USDA) (1993) Soil Survey Manual, Soil Survey Staff, Natural Resource  
491 Conservation Service, Handbook No. 18, U.S. Government Printing Office, Washington; p 437.
- 492 [37] Zube E, Sell J, Taylor J (1982) Landscape perception: Research, application and theory. *Landsc. Plan.* 9: 1–  
493 33.
- 494 [38] Bouraoui F, Vachaud G, Treut L, Chen T (1999) Evaluation of the impact of climate changes on water  
495 storage and groundwater recharge at the watershed scale. *Clim Dyn* 15:153–161.
- 496 [39] Potter R.B, Darmame K, Barham, N., Nortcliff S. (2009) “Ever-growing Amman”, Jordan: Urban  
497 expansion, social polarisation and contemporary urban planning issues. *Habitat Int.* 33: 81–92.
- 498 [40] Jyrkama M, Sykes J, Normani S (2005) Recharge Estimation for Transient Ground Water Modeling.  
499 *Ground Water* 40:638–648.
- 500 [41] Horowitz A (2001) The Jordan Rift Valley; Balkema: Rotterdam, The Netherlands, p. 730.
- 501 [42] Odeh T, Geyer S, Rödiger T, Siebert C, Schirmer M (2013) Groundwater chemistry of strike slip faulted  
502 aquifers: the case study of Wadi Zerka Ma'in aquifers, north east of the Dead Sea. *Environ Earth Sci*  
503 70:393–406.