



# NOW® Grey Primer

I21218007

PRODUCT DESCRIPTION	APPLICATION	CAUTIONS
<p>Fast drying and durable primer that inhibits rust and can be used on indoor or outdoor surfaces.</p>	<p>Surface must be cleaned of rust, grease, wax, moisture, etc. Shake until ball within begins to rattle, then shake for an additional 2 minutes. Hold can 12"-14" from object. Should additional coats be desired, allow 15 minutes before respraying. Dries to touch in 12 minutes. Clean valve immediately after use by turning can upside down and spraying until clear gas comes out. If spray button becomes clogged, wear eye protection, wipe off the button opening with lacquer thinner.</p>	<p><b>CONTAINS ACETATES AND KETONES. DANGER! EXTREMELY FLAMMABLE.</b> Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. <b>DO NOT SMOKE</b> — Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. <b>CONTENTS UNDER PRESSURE.</b> Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. <b>VAPOR HARMFUL.</b> Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. <b>FIRST AID:</b> In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. <b>DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.</b> Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. <b>WARNING:</b> This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. <b>DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</b></p>
PAINTING CONDITIONS	CHARACTERISTICS	
<p>Spray outdoors or in a well-ventilated area. Protect surrounding areas. Best results when temperature is 55°F (12° C) to 75°F (24°C) and humidity is below 60%.</p>	<p><b>Color:</b> Grey Primer</p> <p><b>Coverage:</b> 10-12 sq. ft. on a solid non-porous surface.</p> <p>Drying Time, @ 77 °F, 50% RH: Drying time and recoat times are temperature, humidity, and film thickness dependent</p> <p><b>To Touch:</b> 12 minutes <b>Re coat:</b> 15 minutes</p>	
SURFACE PREPARATION	<p><b>Vehicle Type:</b> Acrylic Modified Alkyd <b>Volume Solids:</b> 6.23% <b>Weight Solids:</b> 15.23%</p>	
<p>WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to <a href="http://www.epa.gov/lead">www.epa.gov/lead</a>.</p>		PERFORMANCE TESTING
		<p>Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse. To contact us call 1-800-247-3268 or <a href="mailto:ask@krylon.com">ask@krylon.com</a>.</p>